

## Topward 7060 Series Oscilloscope

<b>Specification</b>	<b>7065A</b>	<b>7066A</b>	<b>7068A</b>
<b>Vertical Axis</b>			
Bandwidth(-3dB)	DC-60MHz、X5MAG：20MHz		
Sensitivity	5Mv / Div-5V / Div±3%、10 Calibrated Steps、X5MAG：1Mv / Div-1V / Div		
Display Mode	CH1、CH2、DUAL(ALT/CHOP)、ADD		
Rise Time	5.8ns		
Input Impedance	1 MΩ / 25PF		
Input Coupling	AC、DC、GND		
Max. Input Volt	400V DC + Peak AC		
<b>Horizontal Axis</b>			
Main Time Base	0.1μS / Div-2S / Div、23 Calibrated Steps、X 10MAG：10Ns / Div-200mS / Div		
Delay Time Base	N/A	Yes	N/A
Delay Display	Main、Mix、Delay		
<b>Trigger</b>			
Mode	Auto、Norm、TV-V、TV-H		
Source	CH1、CH2、ALT、LINE、EXT		
Sensitivity	INT：0.5DIV、EXT：0.5V		
Polarity	+、-		
Level	Adjustable		
Hold Off	Yes		
<b>X-Y</b>			
Mode	CH1：X、CH2：Y		
Sensitivity	5mV / Div-5V / Div		
Bandwidth(-3dB)	DC-1MHz		
Phase Difference	3° at 50KHz		
<b>Z Axis</b>			
Z Modulation	N/A	Yes	N/A
<b>CRT</b>			
Cursor Readout	N/A	N/A	Yes
Screen	6 inch Rectangular、Internal Graticule with % Scale		
Effective Area	8 * 10 cm		
Acceleration Voltage	12KV		
Illumination	N/A	Yes	N/A
<b>General</b>			
CH2 Output	N/A	Yes	Yes
Component Test	N/A	Yes	N/A
Beam Find	N/A	Yes	N/A
Calibrator	Square Wave、1KHz±10%、2Vp-p±3%		0.5Vp-p±3%
Trace Rotation	Electrical、Front Panel Adjustable		
Dimension	324(L) * 132(W) * 398(H)mm		
Net / Gross Weight	7.8Kg / 12Kg		
Power	115V / 230V± 10%、50 / 60 Hz		